



EVO Permanent Linemarking Paint

Product Code: **LM00010**

Pack Quantity: **12**

EVO Tool Permanent Linemarking Paints are high-quality acrylic paints, designed for use with both trolley and manual applications.

They are versatile and suitable for a variety of surfaces, including asphalt, concrete, gravel, and grass.

PRODUCT FEATURES

- 750ml
- Acrylic paints with a blend of high-quality pigments, resins, and fast-drying solvents
- Can be applied either by hand or as a spot marker, or alternatively used in conjunction with a line marking applicator
- Propane, butane, lead, and Cadmium free
- Wet and dry applications
- Suitable for use on asphalt, concrete, gravel, and grass
- Dry in 30 mins and fully cured in 24 hours
- Boxed in 12's

DIRECTIONS FOR USE

- Check surface to be marked is dry and free from dust and grease
- Shake can vigorously until shaker ball moves and for 30 seconds afterwards
- Holding the aerosol closer to the ground will create a more accurate and dense line
- After use spray the aerosol upright (away from eyes and other obstacles). This will clear the nozzle

COLOURS

RED	LM00010
WHITE	LM00020
YELLOW	LM00030
BLUE	LM00040
GREEN	LM00050
ORANGE	LM00060
BLACK	LM00070

DANGER

- Extremely flammable aerosol
- Pressurised container: May burst if heated
- Repeated exposure may cause skin dryness or cracking
- Causes serious eye irritation
- May cause drowsiness or dizziness
- Harmful to aquatic life with long-lasting effects.
- Keep out of the reach of children
- Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking
- Do not spray on an open flame or other ignition sources.
- Do not pierce or burn, even after use
- Do not breathe vapour /spray
- Wear protective gloves/eye protection
- Use only outdoors or in well-ventilated areas
- Contains: Acetone, Hydrocarbons, C9, aromatics, n-butyl acetate



IF IN EYES

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.

- Seek medical advice / attention if you feel unwell. Protect from sunlight
- Do not expose to temperatures exceeding 50C.
- Dispose of contents and container in accordance with local regulations.

