

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Version 0.0

1.1 Product identifier

Trade name Contact Adhesive Spray 1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company	: CID Trading LTD
	Unit 10,
	Peckfield Business Park, Phoenix Avenue, Leeds, LS25 4DY
Telephone	: +44 113 201 1340
E-mail address	: sales@cidgroup.co.uk

1.4 Emergency telephone number

Emergency telephone num- : +44 113 201 1340 (office hours only) ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product :	Mixture	
Classification (REGULATION (EC) No 127	2/2008)
Aerosols, Category 1		H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2		H315: Causes skin irritation.
Eye irritation, Category 2		H319: Causes serious eye irritation.
Specific target organ toxicity - sin posure, Category 3, Central nerv system	0	H336: May cause drowsiness or dizziness.
Chronic aquatic toxicity, Catego	ry 3	H412: Harmful to aquatic life with long lasting ef- fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) Country GB 10000006978

SAFETY DATA SHEET

Contact Adhesive Spray

according to Regulation (EC) No. 1907/2006

CONSIDER IT DONE "

Revision Date 10.07.2017 Version 0.0 Print Date 10.07.2017 Hazard pictograms Signal word Danger ÷ Hazard statements H222 Extremely flammable aerosol. ÷ H229 Pressurised container: May burst if heated. H315 Causes skin irritation. H319 Causes serious eve irritation. H336 May cause drowsiness or dizziness. Harmful to aquatic life with long lasting ef-H412 fects. If medical advice is needed, have product Precautionary statements : P101 container or label at hand. P102 Keep out of reach of children. Prevention: Keep away from heat, hot surfaces, sparks, P210 open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. **Disposal:** P501 Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

• 200-662-2 acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
acetone	Flam. Liq.2; H225	>= 10 - < 20

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006



Contact Adhesive Spray

Revision Date 10.07.2017

Version 0.0

Print Date 10.07.2017

67-64-1 200-662-2 01-2119471330-49-XXXX	Eye Irrit.2; H319 STOT SE3; H336	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 921-024-6 01-2119475514-35-XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 10 - < 20
Substances with a workplace exposure limit :		
petroleum gases, liquefied 68476-85-7 270-704-2	Flam. Gas1; H220	>= 25 - < 40

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms and	d effects, both acute and delayed
Symptoms	: Excessive lachrymation Erythema Dermatitis Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms.
Risks	: irritant effects



Version 0.0 Print Date 10.07.2017

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	: Water

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-	: No hazardous combustion products are known
ucts	

5.3 Advice for firefighters

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Use personal protective equipment.
	Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

6.4 Reference to other sections

For personal protection see section 8.



SECTION 7: Handling and storage

7.1 Precautions for safe handling	
Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drink- ing should be prohibited in the application area. Take precau- tionary measures against static discharge. Open drum careful- ly as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	: Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, in	cluding any incompatibilities
Requirements for storage areas and containers	: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red- hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.
Other data	: No decomposition if stored and applied as directed.
7.3 Specific end use(s)	

Version 0.0

Specific use(s)

: No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parame- ters *	Basis *
petroleum gases, liquefied	68476-85-7	TWA	1.000 ppm 1.750 mg/m3	GB EH40
		STEL	1.250 ppm 2.180 mg/m3	GB EH40
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	GB EH40

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Contact Adhesive Spray



Revision Date 10.07.2017

Version 0.0

Print Date 10.07.2017

GB EH40 3	1.500 ppm 3.620 mg/m3	STEL		
--------------	--------------------------	------	--	--

8.2 Exposure controls

Personal protective equipment				
Eye protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water			
Hand protection	 Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. 			
Skin and body protection	: Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).			
Respiratory protection	 Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. 			
Environmental exposure controls				
General advice	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.			

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties				
Appearance	Aerosol containing a compressed gas			
Colour	:	amber		

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 **Contact Adhesive Spray**

Re



Revision Date 10.07.2017		Version 0.0	Print Date 10.07.2017
Odour	:	characteristic	
Odour Threshold	:	No data available	
Flash point	:	-60 °C	
Autoignition temperature	:	No data available	
Decomposition temperature	:	No data available	
Lower explosion limit	:	0 %(V)	
Upper explosion limit	:	13 %(V)	
Flammability	:	No data available	
Explosive properties	:	No data available	
Oxidizing properties	:	No data available	
рН	:	7	
Melting point/range / Freez- ing point	:	No data available	
Boiling point/boiling range	:	No data available	
Vapour pressure	:	34,6637 hPa	
Density	:	0,84 g/cm3 at 20 °C	
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Viscosity, dynamic	:	No data available	
Viscosity, kinematic	:	20,5 mm2/s	
Relative vapour density	:	No data available	
Evaporation rate	:	No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.



Version 0.0



Version 0.0 Print Date 10.07.2017

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Revision Date 10.07.2017

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity					
Not classified based on availa	able information.				
Components:					
acetone:					
Acute oral toxicity	: LD50 Oral (Rat): 5.800 mg/kg				
Acute inhalation toxicity	: LC50 (Rat): 76 mg/l Exposure time: 4 h Test atmosphere: vapour				
Acute dermal toxicity	: LD50 Dermal (Rabbit): 20.000 mg/kg				
Skin corrosion/irritation					
Causes skin irritation.					
Serious eye damage/eye irr	itation				
Causes serious eye irritation.					
Respiratory or skin sensitisation					
Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.					
Germ cell mutagenicity					
Not classified based on available information.					
Carcinogenicity					
Not classified based on available information.					

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.



STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Co	m	po	ne	nts	

acetone :	
Toxicity to fish	: LC50: > 5.000 mg/l, 96 h, Fish
Toxicity to daphnia and other aquatic invertebrates	: EC50: 12,700 mg/l, 48 h, Daphnia (water flea)
Toxicity to algae	: ErC50: > 530 mg/l, 96 h, Pseudokirchneriella subcapitata (green algae)

Version 0.0

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-	: An environmental hazard cannot be excluded in the event of
mation	unprofessional handling or disposal.
	Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Contact Adhesive Spray



Revision Date 10.07.2017 Product Version 0.0

Print Date 10.07.2017

: The generation of waste should be avoided or minimized

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Contact Adhesive Sprav



Revision	Date 10.07.2017

	 wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Contaminated packaging	: 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

ADR 14.1 UN number 14.2 UN proper shipping name 14.3 Transport hazard class(es) Classification Code Labels Tunnel restriction code 14.5 Environmental hazards	: 1950 : AEROSOLS : 2 : 5F : 2.1 : (D) : no
IATA 14.1 UN number 14.2 UN proper shipping name 14.3 Transport hazard class(es)	: 1950 : Aerosols, flammable : 2.1
Labels 14.5 Environmental hazards	: 2.1 : no
IMDG 14.1 UN number 14.2 UN proper shipping name 14.3 Class Labels EmS Number 1 EmS Number 2 14.5 Marine pollutant	: 1950 : AEROSOLS : 2.1 : 2.1 : F-D : S-U : no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable



SECTION 15: Regulatory information

	Safety, health and environmer	ntal regulations/legislation	n specif	fic for the subst	ance or mixture
F t	Prohibition/Restriction: Banned and/or restrictedREACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII): Banned and/or restricted (petroleum gases, liquefied)				
	REACH - Candidate List of Subs Concern for Authorisation (Articl		: None of the components are listed (=> 0.1 %).		
	REACH - List of substances sub (Annex XIV)	ject to authorisation	: Not a	applicable	
I	REACH Information: All substances contained in our Products are - preregistered or registered by our upstream suppliers, and/or - preregistered or registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.				
	Seveso III: Directive 2012/18/EL or-accident hazards involving da		nt and o		
	18	Liquefied extremely flan mable gases (including LPG) and natural gas	n-	Quantity 1 50 t	Quantity 2 200 t
I	P3a	FLAMMABLE AEROSC	OLS	150 t	500 t
:	34	Petroleum products: (a) gasolines and naphthas (b) kerosenes (including fuels), (c) gas oils (inclu ing diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) altern tive fuels serving the sa purposes and with simili- properties as regards flammability and enviror mental hazards as the products referred to in points (a) to (d)	s, g jet id- na- ame ar	2.500 t	25.000 t
Ň	VOC-CH (VOCV)	: 50 %			
Ň	VOC-EU (solvent)	: 50 %			

Version 0.0



If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Version 0.0

Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	 Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.
Other regulations	: 75/324/EEC

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic Asp. Tox. Eye Irrit. Flam. Gas Flam. Liq. Skin Irrit. STOT SE ADR	Chronic aquatic toxicity Aspiration hazard Eye irritation Flammable gases Flammable liquids Skin irritation Specific target organ toxicity - single exposure Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic



Contact Adnesive Spray			
Revision Date 10.07.2017	Version 0.0	Print Date 10.07.2017	
PNEC	Predicted no effect concentration		
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a		
	European Chemicals Agency		
SVHC	Substances of Very High Concern		
vPvB	Very persistent and very bioaccumulative		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall _apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !